

EXPRESS MAIL LABEL NO: TB244296569 US
DATE OF DEPOSIT: APRIL 30, 1993

HIGH DENSITY INTEGRATED CIRCUIT APPARATUS, TEST
PROBE AND METHODS OF USE THEREOF

FIELD OF THE INVENTION

This invention relates to an apparatus and test probe for integrated circuit devices and methods of use thereof.

BACKGROUND OF THE INVENTION

In the microelectronics industry, before integrated circuit (IC) chips are packaged in an electronic component, such as a computer, they are tested. Testing is essential to determine whether the integrated circuit's electrical characteristics conform to the specifications to which they were designed to ensure that electronic component performs the function for which it was designed.

Testing is an expensive part of the fabrication process of contemporary computing systems. The functionality of every I/O for contemporary integrated circuit must be tested since a failure to achieve the design specification at a single I/O can render an integrated circuit unusable for a specific application. The testing is commonly done both at room temperature and at elevated temperatures to test

2

40993-028

IBM Confidential

functionality and at elevated temperatures with forced voltages and currents to burn the chips in and to test the reliability of the integrated circuit to screen out early failures.

Contemporary probes for integrated circuits are expensive to fabricate and are easily damaged. Contemporary test probes are typically fabricated on a support substrate from groups of elongated metal conductors which fan inwardly towards a central location where each conductor has an end which corresponds to a contact location on the integrated circuit chip to be tested. The metal conductors generally cantilever over an aperture in the support substrate. The wires are generally fragile and easily damage and are easily displaceable from the predetermined positions corresponding to the design positions of the contact locations on the integrated circuit being tested. These probes last only a certain number of testing operations, after which they must be replaced by an expensive replacement or reworked to recondition the probes.

Figure 1 shows a side cross-sectional view of a prior art probe assembly 2 for probing integrated circuit chip 4 which is disposed on surface 6 of support member 8 for integrated circuit chip 4. Probe assembly 2 consists of a dielectric substrate 10 having a central aperture 12 therethrough. On surface 14 of substrate 10 there are disposed a plurality of electrically conducting beams which extend towards edge 18 of aperture 12. Conductors 16 have ends 20 which bend downwardly in a direction generally perpendicular to the plane of surface 14 of substrate 10. Tips 22 of downwardly projecting electrically conducting ends 20 are disposed in electrical contact with contact locations 24 on surface 25 of integrated circuit chip 4. Coaxial cables 26 bring electrical signals, power and ground through electrical connectors 28 at periphery 30 of substrate 10. Structure 2 of Figure 1 has the disadvantage of being expensive to fabricate and of having fragile inner ends 20 of electrical conductors 16. Ends 20 are easily damaged through use in probing electronic devices. Since the probe 2 is expensive to

Y0993-028 DPM

00000394 000190
00000000 00000000

fabricate, replacement adds a substantial cost to the testing of integrated circuit devices. Conductors 16 were generally made of a high strength metal such as tungsten to resist damage from use. Tungsten has an undesirably high resistivity.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved high density test probe, test apparatus and method of use thereof.

It is another object of the present invention to provide an improved test probe for testing and burning-in integrated circuits.

It is another object of the present invention to provide an improved test probe and apparatus for testing integrated circuits in wafer form and as discrete integrated circuit chips.

It is an additional object of the present invention to provide probes having contacts which can be designed for high performance functional testing and for high temperature burn in applications.

It is yet another object of the present invention to provide probes having contacts which can be reworked several times by resurfacing some of the materials used to fabricate the probe of the present invention.

It is a further object of the present invention to provide an improved test probe having a probe tip member containing a plurality of elongated conductors each ball bonded to electrical contact locations on space transformation substrate.

Advantages

4

In another more particular aspect of the present invention, the test probe is part of a test apparatus and test tool.

Another broad aspect of the present invention is a method of fabricating the probe tip of the probe according to the present invention wherein a plurality of elongated conductors are bonded to contact locations on a substrate surface and project away therefrom.

In a more particular aspect of the method according to the present invention, the elongated conductors are wire bonded to contact locations on the substrate surface. The wires project preferably at a nonorthogonal angle from the contact locations.

In another more particular aspect of the method of the present invention, the wires are bonded to the contact locations on the substrate are embedded in a elastomeric material to form a probe tip for the structure of the present invention.

In another more particular aspect of the present invention, the elongated conductors are embedded in an elastomeric material.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic cross-section of a conventional test probe for an integrated circuit device.

Figure 2 is a schematic diagram of one embodiment of the probe structure of the present invention.

Y0993-028

[illegible]

Figure 5 is an enlarged view of the probe tip within dashed circle 100 of Figures 2 or 3.

Figures 7-13 show the process for making the structure of Figure 5.

Figure 15 shows the elongated conductors of the probe tip fixed by solder protuberances to contact locations on a space transformation substrate.

Figure 17 shows both interposer 76 and probe tip 40 rigidly bonded to space transformer 60.

Add Cl.

77098-028

IBM Confidential

DETAILED DESCRIPTION

Turning now to the figures, Figures 2 and 3 show two embodiments of the test assembly according to the present invention. Numerals common between Figures 2 and 3 represent the same thing. Probe head 40 is formed from a plurality of elongated electrically conducting members 42 embedded in a material 44 which is preferably an elastomeric material 44. The elongated conducting members 42 have ends 46 for probing contact locations on integrated circuit devices 48 of wafer 50. In the preferred embodiment, the workpiece is an integrated circuit such as a semiconductor chip or a semiconductor wafer having a plurality of chips. The workpiece can be any other electronic device. The opposite ends 52 of elongated electrical conductors 42 are in electrical contact with space transformer (or fan-out substrate) 54. In the preferred embodiment, space transformer 54 is a multilevel metal/ceramic substrate, a multilevel metal/polymer substrate or a printed circuit board which are typically used as packaging substrates for integrated circuit chips. Space transformer 54 has, in the preferred embodiment, a surface layer 56 comprising a plurality of thin dielectric films, preferably polymer films such as polyimide, and a plurality of layers of electrical conductors, for example, copper conductors. A process for fabricating multilayer structure 56 for disposing it on surface 58 of substrate 60 to form a space transformer 54 is described in US patent application Serial No. 07/695,368, filed on May 3, 1991, entitled "MULTI-LAYER THIN FILM STRUCTURE AND PARALLEL PROCESSING METHOD FOR FABRICATING SAME" which is assigned to the assignee of the present invention, the teaching of which is incorporated herein by reference. Details of the fabrication of probe head 40 and of the assembly of probe head 40 and 54 will be described herein below.

As shown in Figure 2, on surface 62 of substrate 60, there are, a plurality of pins 64. Surface 62 is opposite the surface 57 on which probe head 40 is disposed.

XC993025

7.

IBM Confidential

00003204 DEC 90

Pins 64 are standard pins used on integrated circuit chip packaging substrates. Pins 64 are inserted into socket 66 or plated through-holes in the substrate 68 which is disposed on surface 70 of second space transformer 68. Socket 66 is a type of pin grid array (PGA) socket such as commonly disposed on a printed circuit board of an electronic computer for receiving pins from a packaging substrate. Second space transformer 68 can be any second level integrated circuit packaging substrate, for example, a standard printed circuit board. Socket 66 is disposed on surface 70 of substrate 68. On opposite surface 70 of substrate 68 there are disposed a plurality of electrical connectors to which coaxial cables 72 are electrically connected. Alternatively, socket 68 can be a zero insertion force (ZIF) connector or the socket 68 can be replaced by through-holes in the substrate 68 wherein the through-holes have electrically conductive material surrounding the sidewalls such as a plated through-hole.

In the embodiment of Figure 3, the pin 64 and socket 66 combination of the embodiment of Figure 2 is replaced by an interposer, such as, elastomeric connector 76. The structure of elastomeric connector 76 and the process for fabricating elastomeric connector 76 is described in copending US patent application Serial No. 07/963,364 to B. Beaman et al., filed October 19, 1992, entitled "THREE DIMENSIONAL HIGH PERFORMANCE INTERCONNECTION MEANS", which is assigned to the assignee of the present invention, the teaching of which is incorporated herein by reference and of which the present application is a continuation-in-part thereof, the priority date of the filing thereof being claimed herein. The elastomeric connector can be opted to have one end permanently bonded to the substrate, thus forming a FRU (field replacement unit) together with the probe/substrate/connector assembly.

Figure 4 shows a cross-sectional view of structure of the elastomeric connector 76 of Figure 3. Connector 76 is fabricated of preferably elastomeric material 78 having opposing, substantially parallel and planar surfaces 80 and 82. Through

YO993-028

69

The entire assembly of second space transformer 68 and first space transformer with probe head 40 is held in place with respect wafer 50 by assembly holder 94 which is part of an integrated circuit test tool or apparatus. Members 82, 84 and 90 can be made from materials such as aluminum.

Figure 5 is an enlarged view of the region of Figures 2 or 3 closed in dashed circle 100 which shows the attachment of probe head 40 to substrate 60 of space transformer 54. In the preferred embodiment, elongated conductors 42 are preferably wires which are at a non-orthogonal angle with respect to surface 87 of substrate 60. At end 102 of wire 42 there is preferably a flattened protuberance 104 which is bonded (by wire bonding, solder bonding or any other known bonding technique) to electrically conducting pad 106 on surface 87 of substrate 60. Elastomeric material 44 is substantially flush against surface 87. At substantially oppositely disposed planar surface 108 elongated electrically conducting members 42 have an end 110. In the vicinity of end 110, there is optimally a cavity 112 surrounding end 110. The cavity is at surface 108 in the elastomeric material 44.

Figure 6 shows the structure of Figure 5 used to probe integrated circuit chip 114 which has a plurality of contact locations 116 shown as spheres such as a Q4 solder balls. The ends 110 of conductors 42 are pressed in contact with contact locations 116 for the purpose of electrically probing integrated circuit 114. Cavity 112 provides an opening in elastomeric material 44 to permit ends 110 to be pressed towards and into solder mounds 116. Cavity 112 provides a means for solder mounds 116 to self align to ends 110 and provides a means containing solder mounds which may melt, seep or be less viscous when the probe is operated at an elevated temperature. When the probe is used to test or burn-in

7/19/78

11

IBM Confidential

11

0000304-050108

Cutting the wire 130 while it is suspended is not done in conventional wire bonding. In conventional wire bonding, such as that used to fabricate the electrical connector of US Patent 4,998,885, where, as shown in Figure 8 thereof, one end a wire is ball bonded using a wire bonded to a contact location on a substrate bent over a loop post and the other of the wire is wedge bonded to an adjacent contact location on the substrate. The loop is severed by a laser as shown in Figure 6 and the ends melted to form balls. This process results in adjacent contact locations having different types of bonds, one a ball bond the other a wedge bond. The spacing of the adjacent pads cannot be less than about ~ 20 mils because of the need to bond the wire. This spacing is unacceptable to fabricate a high density probe tip since dense integrated circuits have pad spacing less than this amount. In contradistinction, according to the present invention, each wire is ball bonded to adjacent contact locations which can be spaced less than 5 mils apart. The wire is held tight and knife edge 134 notches the wire leaving upstanding or flying leads 120 bonded to contact locations 106 in a dense array.

When the wire 130 is severed there is left on the surface 122 of pad 106 an angled flying lead 120 which is bonded to surface 122 at one end and the other end projects outwardly away from the surface. A ball can be formed on the end of the wire 130 which is not bonded to surface 122 using a laser or electrical discharge to melt the end of the wire. Techniques for this are described in co-pending US patent application Serial No. 07/963,346, filed October 19, 1992, which is incorporated herein by reference above.

Figure 10 shows the wire 126 notched (or nicked) to leave wire 120 disposed on surface 122 of pad 106. The wire bond head 124 is retracted upwardly as indicated by arrow 136. The wire bond head 124 has a mechanism to grip and release wire 126 so that wire 126 can be tensioned against the shear blade to sever the wire.

121

Figure 16 shows another alternative embodiment of a method to fabricate the structure of Figure 5.

Numerals common between Figures 15 and 16 represent the same thing. End 180 elongated electrical conductor 182 is held against top surface 163 of pad 162 on substrate 160. A beam of light 184 from laser 186 is directed at end 180 of elongated conductor 182 at the location of contact with surface 163 of pad 162. The end 180 is laser welded to surface 163 to form protuberance 186.

In summary, the present invention is directed to high density test probe for testing high density and high performance integrated circuits in wafer form or as discrete chips. The probe contacts are designed for high performance functional testing and for high temperature burn in applications. The probe is formed from an elastomeric probe tip having a highly dense array of elongated electrical conductors embedded in an elastomeric material which is in electrical contact with a space transformer.

027 While the present invention has been described with respect to preferred embodiments, numerous modifications, changes and improvements will occur to those skilled in the art without departing from the spirit and scope of the invention.